

## 35 Series – Low Profile 44"H Double Duty – Deli

- PRODUCT SPECIFICATIONS SHEETS



- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

### Self Contained Remote

SC-CDS35-4L  
R-CDS35-4L

SC-CDS35-6L  
R-CDS35-6L

SC-CDS35-8L  
R-CDS35-8L

Length  
Height  
Depth  
Depth with bottom door  
(Dimensions are +/- 1/4")

50"  
44"  
35-1/2"  
38-1/2"

71"  
44"  
35-1/2"  
38-1/2"

95"  
44"  
35-1/2"  
38-1/2"

- Specification subject to change without notice

## 35 Series – Low Profile 44"H Double Duty – Deli

### Standard Specifications and Optional Features

<b>CONSTRUCTION</b> UL Classified to ANSI/NSF 7 Foamed in place CFC free foam Triple pane insulated front glass-26"H Heavy gauge steel super structure Bottom storage Drain is included for cleaning	<b>FINISHES</b> Satin finish extrusion on doors and door tracks Designer white exterior front and ends Stainless steel mirror trim Stainless steel heavy gauge top – 17" W Designer white exterior rear
<b>INTERIOR</b> Designer white ends Stainless steel heavy gauge mezzanine shelf White aluminum floor ( <i>bottom storage area</i> ) Air insulated baffle ( <i>prevents moisture from dripping into display area</i> ) Epoxy coated main deck shelves	<b>REFRIGERATION</b> Copevap system ( <i>eliminates need for condensate pan</i> ) R134a expansion valve system Gravity coil located at <i>inside top of unit and bottom storage area</i> Self contained system Automatic defrost controlled by time clock-( <i>self contained units only</i> ) Pressure control maintains constant temperatures Remotes available
<b>EXTERIOR</b> Double pane rear removable doors Newly designed rear compression door jamb Removable front grille allows for cleaning Removable rear grille for easy servicing	<b>LIGHTING</b> 2 Rows of T12 lighting at top of unit
<b>ELECTRICAL REQUIREMENTS</b> 115V/60Hz/1Ph Unit must be hard wired UL/CUL listed 115V-12AMP general purpose receptacle ( <i>wired separately</i> )	<p><b><i>Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.</i></b></p> <p><b><i>Important Note: Product must be cooled before being displayed within the case.</i></b></p>

### OPTIONAL FEATURES

Scale stand Paper cutter Stainless steel, laminate, or paint Mirrored doors Extra row of mezzanine shelf	Front bumpers 1" or 3" Door locks Digital thermometer Pass thru front doors Sandwich racks
--	--



## 35 Series – Low Profile 44"H Double Duty – Deli

### Technical Data

Model #	Self contained	SC-CDS35-4L	SC-CDS35-6L	SC-CDS35-8L
	Remote	R-CDS35-4L	R-CDS35-6L	R-CDS35-8L
Length Height Depth Depth with Bottom door (Dimensions are +/- 1/4")		50" 44" 35-1/2" 38-1/2"	71" 44" 35-1/2" 38-1/2"	95" 44" 35-1/2" 38-1/2"
Operating temperature Refrigerant (expansion valve) Compressor size HP Pressure control settings @ 75°F, 55%RH  Defrost per day (24 hours) BTU's at +20°F Evap. Temp. Voltage Amperage Amperage, lights only Cord and plug	Self contained Self contained  CUT IN CUT OUT Air Defrost Remote  Self contained Remote	36°F to 40°F R134a 1/4  30 12 1 per day 1400 115V 6.0A 0.8A No	36°F to 40°F R134a 1/3  30 12 1 per day 2100 115V 8.7A 1.3A No	36°F to 40°F R134a 1/3  30 12 1 per day 2800 115V 9.1A 1.6A No
Exterior color Interior color Floors # of top doors Door size # of bottom doors  Front glass # of coils Bottom storage Main deck shelf # Main deck size Cubic capacity (ft <sup>3</sup> ) Mezzanine shelf	Self contained Remote	White White White 2 19-3/16"X19-3/16" 1 2 26" X 45" 2 Yes 2 22-1/4"X31-5/8" 23 Standard	White White White 2 29-5/8"X19-3/16" 2 3 26" X 66" 2 Yes 3 22-1/4"X31-5/8" 34 Standard	White White White 4 19-3/16"X19-3/16" 3 4 26" X 90" 2 Yes 4 22-1/4"X31-5/8" 45 Standard

### SHIPPING INFORMATION

Height Depth Length Gross weight  Cubic feet	Self contained Remote	58" 44" 61" 480# 434# 89ft <sup>3</sup>	58" 44" 87" 625# 571# 128ft <sup>3</sup>	58" 44" 109" 880# 826# 164ft <sup>3</sup>
---	--------------------------	--	---	--

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Cases are equipped with drains; check your local building codes for connection requirements.
- Specification subject to change without notice